

1: Power line Three-color lines connected with U. V and W phases/ yellow and green wires grounded Temperature control line 110°C thermistor two-phase connected with the temperature-control protector 2: Cooling water yielding (2 and 6 ends terminated with 8/6 hoses) 3:Pole change and dust removal pressure 0.2-0,3Mpa (6/4 hoses) 4: Air seal pressure 0.1-0.2Mpa (6/4 hoses) 5:Tool discharge and air feed pressure 0.70 MPa (6/4 hoses) 6: Cooling influent Pump lift 12m (avoid wrong connection) 7: Quantity of proximity switches Pole hanging and pole discharge NPN (normally open) N.O. Wiring method of the proximity switch Brown wire connected with +24VDC blue wire connected with 0VDC Signal load end connected with +24VDC/the other end connected with the black wire 8: Handle of the lifting sling Installation and use

Model GDL 120-30-18-5.5 Voltage 380 V Power 5.5 kw Current 11.0 A Frequency 600 Hz Rotating speed 18000 rpm 4P Pole number Phase number 3 Rotating direction Rotate anticlockwise from the shaft extension end Tool holder BT30 (Parfaite is recommended) Blind rivet BT30-45° (Parfaite recommended) Weight 25 KG

PTC three-core									
thermistor parameter									
DC power supply	Maximum DC25V/100mA								
-20~25℃	≤300Ω								
≪90℃	≤750₽								
105°C	≤1650₽								
110°C	Rated operating temperature								
115°C	≥3990₽								
≥125℃	≥12K Ω								
≤160℃	Maximum storage temperature								

## Special warning:

1. The electric main shaft shall be installed at the clamped position; otherwise the bearing will be easily damaged!

The main shaft shall entirely stop before the tool changing. The manual tool changing button shall not act during the rotation of the shaft; otherwise it will easily result in the seizure of the shaft!
The compressed air shall be clean and dry, and the filter accuracy shall be 0.1micron! Air seal is normally open. It is recommended to use the two-level filter, and the filter accuracy is 0.5 micron/ 0.1 micron respectively. The air filter is installed with the self-discharge device.
It is required to set the frequency converter strictly according to the frequency-voltage curve of the electric shaft.

is											
		Number of places	Zoning	Modified document number Standardized by	Signature	Date	Phase	e mark	Weight	Scale	Outline diagram
	Reviewed	1									
	by Processed by	1		Approved by			Total page(s)		Page		GDL120-30-18Z/5.5