



- 1: Power line Three-color lines connected with U, V and W phases/ yellow and green wires grounded
- 2: Cooling water yielding (2 and 6 ends terminated with 8/6 hoses)
- 3: Pole change and dust removal pressure 0.2-0.3Mpa (6/4 hoses)
- 4: Air seal pressure 0.1-0.2 Mpa (6/4 hoses)
- 5: Tool discharge and air feed pressure 0.70 MPa (6/4 hoses)
- 6: Cooling influent Pump lift 12m (avoid wrong connection)
- 7: Quantity of proximity switches Pole hanging and pole discharge NPN (normally open) N.O. Wiring method of the proximity switch Brown wire connected with +24VDC blue wire connected with 0VDC Signal load end connected with +24VDC/the other end connected with the black wire
- 8: Handle of the lifting sling Installation and use

Model GDL 120-30-18-5.5
Voltage 380 V
Power 5.5 kw
Current 11.0 A
Frequency 600 Hz
Rotating speed 18000 rpm
Pole number 4P
Phase number 3
Rotating direction Rotate anticlockwise from the shaft extension end
Tool holder BT30 (Parfaite is recommended)
Blind rivet BT30-45° (Parfaite is recommended)
Weight 26.5 KG

Special warning:

1. The electric main shaft shall be installed at the clamped position; otherwise the bearing will be easily damaged!
2. The main shaft shall entirely stop before the tool changing. The manual tool changing button shall not act during the rotation of the shaft; otherwise it will easily result in the seizure of the shaft!
3. The compressed air shall be clean and dry, and the filter accuracy shall be 0.1micron! Air seal is normally open. It is recommended to use the two-level filter, and the filter accuracy is 0.5 micron/ 0.1 micron respectively. The air filter is installed with the self-discharge device.
4. It is required to set the frequency converter strictly according to the frequency-voltage curve of the electric shaft.

PTC three-core thermistor parameter	
DC power supply	Maximum DC25V/100mA
-20~25℃	≤300Ω
≤90℃	≤750Ω
105℃	≤1650Ω
110℃	Rated operating temperature
115℃	≥3990Ω
≥125℃	≥12KΩ
≤160℃	Maximum storage temperature

						Outline diagram of the flange		
Marks	Number of places	Zoning	Modified document number	Signature	Date			
Designed by			Standardized by			Phase mark	Weight	Scale
Reviewed by								
Processed by			Approved by			Total page(s)	Page	
						GDL120-30-18Z/5.5		